

## EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

Tiltable battery-powered LED bar and mood light with 4in1 LEDs and QuickDMX

Art. No.: 41700120

GTIN: 4026397635850



**List price: 367.71 €**

incl. 19% VAT.

### Features:

- 100° tiltable bar with 6 high-power 8 W RGBW LEDs (4in1) and removable frost filter
- Mood light with milky front screen provides a pleasantly soft light with 30 SMD RGBW LEDs (4in1)
- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 13h depending on program used
- 30 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 6 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 15°
- Multicolor LCD display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Silent operation

### Logistic

EAN / GTIN: 4026397635850

Weight: 3,50 kg

Length: 0.55 m

Width: 0.17 m

Height: 0.14 m

- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x frost filter, 1 x remote control, 1 x battery, 1 x omega bracket, 4 x knurled screw, 4 x washer, 1 x declaration of conformity

### Technical specifications:

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz   |
| IP classification:      | IP20   |
| Protection class:       | Protection class I   |
| Power connection:       | Battery/battery pack<br>Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)        |
| Battery pack type:      | 1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh   |
| Battery pack:           | Battery operation up to 13h depending on<br>program used<br><br>Recharging time 4h   |
| Lamp type:              | LED lamp   |
| LED type:               | 30 x 0,25 W SMD 5050 4in1 QCL RGBW<br>(homogenous color mix)<br><br>6 x 8 W high-power 4in1 QCL RGBW<br>(homogenous color mix) |
| DMX channels:           | 3; 7; 8; 9; 11   |
| DMX input:              | 3-pin XLR (M) mounting version   |
| DMX output:             | 3-pin XLR (F) mounting version   |
| Cooling:                | Passive convection cooling   |
| Control:                | Stand-alone; DMX; QuickDMX; IR remote control;<br>sound to light via microphone; master/slave<br>function                      |
| Preprogrammed in:       | LED PC-Control 512; Light Captain; EASY<br>SHOW 1; EASY SHOW 2; EASY SHOW 3;<br>Colorchief                                     |
| Projection:             | Flicker-free   |
| Carrier frequency:      | 2,4 GHz  |
| Beam angle:             | 15°  |
| Beam angle (1/2 peak):  | 15°  |
| Beam angle (1/10 peak): | 30°  |
| Housing color:          | Black  |
| Display type:           | Multicolor LCD display   |
| Theft protection:       | KENSINGTON LOCK  |
| Dimensions:             | Length: 41,1 cm<br>Depth: 9,5 cm<br>Height: 10,5 cm  |
| Weight:                 | 2,80 kg  |
| Noise classification:   | Class 0 (no noise at all)  |
| Remote control          |  |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese<br>built-in   |
| Legal specifications    |  |
| Special product:        | Not designed for household room illumination   |

Intended use:

Show effect lighting

---