

EUROLITE AKKU UP-1 QCL Flex Spot QuickDMX

LED uplight with 15 W 4in1 LED, tiltable head and QuickDMX transceiver

Art. No.: 41700505

GTIN: 4026397584646



List price: 284.41 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Inclination angle of the LED head manually adjustable
- Interchangeable front lens for 9° or 15° beam angle
- Battery operation up to 18h depending on program used
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 9°
- For application areas such as: Mobile djs / entertainer; wedding/gala/events; mobile use; small rental
- Dimmer speed (step response) adjustable; colors preset; color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x external mains adapter, 1 x remote control, 2 x battery, 1 x lens, 1 x omega bracket, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397584646

Weight: 2,46 kg

Length: 0.24 m

Width: 0.18 m

Height: 0.18 m

Technical specifications:

Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 7,4 V, 8800 mAh, 65,12 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 6h
Lamp type:	LED lamp
LED type:	1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9° 15°
Beam angle (1/10 peak):	18° 30°
Housing color:	Black
Dimensions:	Width: 12 cm Depth: 12 cm Height: 14,2 cm
Weight:	2,21 kg
Noise classification:	Class 0 (no noise at all)
External mains adapter	
Power supply:	100-240 V AC, 50/60 Hz 8,4V 3000 mA
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting