

EUROLITE AKKU IP PAR 7 QCL WDMX

IP65 battery-powered spotlight with RGBW LEDs, WDMX, frost filters and IR remote control

Art. No.: 41700790

GTIN: 4026397676730



The article is no longer in our assortment.

Features:

- Integrated W-DMX transceiver for wireless DMX Control
- Two additional frost filters provide a soft, homogeneous light
- Battery operation up to 9h depending on program used
- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; W-DMX by wireless solution; stand-alone; IR remote control; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 8°
- With double bracket
- OLED display
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; stage

Logistic

EAN / GTIN: 4026397676730

Weight: 5,60 kg

Length: 0.23 m

Width: 0.24 m

Height: 0.34 m

- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x frost filter, 2 x screw, 1 x declaration of conformity, 2 x mounting bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 25,9 V, 7800 mAh, 202,02 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; W-DMX by wireless solution; stand-alone; IR remote control; master/slave function; sound to light via microphone
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	8°
Beam angle (1/2 peak):	8° Frost filter 15° Frost filter 19°
Beam angle (1/10 peak):	15° Frost filter 31° Frost filter 43°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 23,4 cm Depth: 28,0 cm

	Height: 17,0 cm
Weight:	5,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting