

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

Art. No.: 41700800

GTIN: 4026397676167



List price: 712.81 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 26h depending on program used
- 14 powerful LEDs 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
- Variable color temperature 2700 K - 8000 K
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use
- Preprogrammed in LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- Mains input and output for power linking up to 8 units
- Silent operation
- Cordless, flexible and versatile
- For application areas such as: Mobile use; stage; rental
- Application possibility: Standing; suspended; on stand

Package contents

Logistic

EAN / GTIN: 4026397676167

Weight: 9,10 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x XLR cable, 3 x frost filter, 2 x screw

Technical specifications:

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack built-in Via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1,1 m |
| Power output: | IP T-Con (F) mounting version |
| Fuse: | 5 x 20 mm, T 3 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 26h depending on program used Recharging time 3h |
| LED type: | 14 x 10 W 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Frost filter |
| DMX channels: | 2; 3; 6-1; 6-2; 12 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control; master/slave function; QuickDMX |
| Preprogrammed in: | LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° 27° 30° 60° |
| Color temperature: | 2700K - 8000K adjustable |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Dimensions: | Width: 31,7 cm Depth: 22,7 cm Height: 37,0 cm |
| Weight: | 7,85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |

Battery: 1 x button cell 3.0 V CR2032 lithium manganese
built-in

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
