

EUROLITE AKKU IP Tourlight 200 RGB+WW

Silent IP65 battery powered spotlight with RGB+WW color mixture, QuickDMX, CRI >90

Art. No.: 41700900

GTIN: 4026397705096



List price: 712.81 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 20h depending on program used
- 1 powerful LED 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Dimmer electronic; color blend stepless
- 9 integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; master/slave function
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- With a beam angle of 30°
- Variable color temperature 1800 K - 8000 K
- Very high color rendering index (CRI)
- With omega bracket; with double bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Stage; mobile use; theater; rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397705096

Weight: 6,30 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.39 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Device fuse:	5 x 20 mm, T fuse serviceable
Battery pack type:	1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh
Battery pack:	Battery operation up to 20h depending on program used Recharging time 4,5h
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; master/slave function
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	60°
Color temperature:	1800K - 8000K adjustable
Color rendering index (CRI):	93 Ra
Housing color:	Black
Attachment system:	Omega bracket Double bracket
Display type:	LCD display
Dimensions:	Width: 25,1 cm Depth: 27,2 cm Height: 32,7 cm Diameter: Ø 18,2 cm
Weight:	5,85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting
