

EUROLITE LED KLS-120 Laser FX II Compact Light Set

DMX light effect bar with 2 rotating LED derbies, 2 LED spots and 2 lasers (RG/2M)

Art. No.: 42109650

GTIN: 4026397689358



List price: 355.81 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- Direct color selection for 15 preset colors
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 7 integrated show programs
- Flicker-free
- The device is cooled by passive convection cooling
- 4 digit 7-segment LED display
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Mains input and output for power linking up to 8 units
- Application possibility: On stand; suspended
- For application areas such as: Mobile use; party room; mobile djs / entertainer; small rental
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Rubber feet
- Silent operation
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 powerful LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)-
 spots controlled separately
- With a beam angle of 18°

Logistic

EAN / GTIN: 4026397689358
Weight: 5,80 kg
Length: 0.67 m
Width: 0.17 m
Height: 0.35 m

light effect

- 4 powerful LEDs 3 W high-power R/G/B/W
 spots controlled separately

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Device fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	3; 13; 25
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 62,5 cm Depth: 15,5 cm Height: 22,9 cm
Weight:	4,60 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Spotlight	
LED type:	3 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	34
Light effect	
LED type:	4 x 3 W high-power R/G/B/W
Laser	

Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 14 mW Red (R) 40 mW
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting