eurolite®

EUROLITE LED Party Panel RGB+UV

LED party panel with RGB+UV color mixing and DMX

Art. No.: 42110199 GTIN: 4026397630749











List price: 83.18 €

incl. 19% VAT.

Features:

- 9 powerful LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Flicker-free
- With double bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 15°
- For application areas such as: Party room; small rental
- Silent operation
- Application possibility: Suspended; on stand
- Package contents
- 1 x spotlight, 1 x remote control, 1 x battery, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	13 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397630749 Weight: 0,89 kg Length: 0.20 m Width: 0.20 m Heigth: 0.12 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection: Fixed power supply cord with Euro plug Fuse: Fuse serviceable Lamp type: LED lamp LED type: 9 x 4 W high-power fin1 QCL RGB/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 3; 4; 4; 8 DMX output: 1 x 3-pin XLR (M) mounting version Cooling: Passive convection cooling Control: Stand-alone: DMX; sound to light via microphone; IR remote control Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dirensions: Width: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² HO5VVH2-F Cable length: Approx. 1, 1 m Mounting bracket Diameter mounting holes: Diameter mounting holes	Protection class:	Protection class II
Lamp type: LED lamp LED type: 9 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 3; 4; 4; 8 DMX output: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone: DMX; sound to light via microphone; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F	Power connection:	Fixed power supply cord with Euro plug
LED type: 9 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 3; 4; 4; 8 DMX output: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; IR remote control Preprogrammed in: Light'1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0.75 kg Noise classification: 2 x 0.75 mm² H05VVH2-F Cable construction: 2 x 0.75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Materia1: Metal, 1,4 mm <	Fuse:	Fuse serviceable
Image: Control of the second	Lamp type:	LED lamp
DMX channels: 3; 4; 4; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; IR remote control Preprogrammed in: Light J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5, 1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control	LED type:	
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; IR remote control Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5, 1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Leg	Flash rate:	0 - 20 Hz
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; IIR remote control Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications	DMX channels:	3; 4; 4; 8
Cooling:Passive convection coolingControl:Stand-alone: DMX; sound to light via microphone; IR remote controlPreprogrammed in:Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; ColorchiefProjection:Flicker-freeBeam angle:15°Beam angle (1/10 peak):11°Housing color:BlackAttachment system:Double bracketDisplay type:4 digit 7-segment LED displayMaterial:PlasticDimensions:Widh: 15 cm Depth: 5,1 cm Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordCable construction:Cable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:Diameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlEastery:Lagal specificationsSpecial product:Not designed for household room illumination	DMX input:	1 x 3-pin XLR (M) mounting version
Control: Stand-alone; DMX; sound to light via microphone; IR remote control Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	DMX output:	1 x 3-pin XLR (F) mounting version
IR remote control Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:	Cooling:	Passive convection cooling
EASY SHOW 2; EASY SHOW 3; ColorchiefProjection:Flicker-freeBeam angle:15°Beam angle (1/2 peak):15°Beam angle (1/10 peak):31°Housing color:BlackAttachment system:Double bracketDisplay type:4 digit 7-segment LED displayMaterial:PlasticDimensions:Width: 15 cm Depth: 5,1 cm Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cord2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:1 x Ø11mmMaterial:Material:Netal, 1,4 mmRemote control1 x button cell 3.0 V CR2025 lithium manganese built-inSpecial product:Not designed for household room illumination	Control:	
Beam angle: 15° Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Z x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:	Preprogrammed in:	
Beam angle (1/2 peak): 15° Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord 2 x 0,75 mm² H05VVH2-F Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak): 31° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:	Beam angle:	15°
Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Eastery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:	Beam angle (1/2 peak):	15°
Attachment system:Double bracketDisplay type:4 digit 7-segment LED displayMaterial:PlasticDimensions:Width: 15 cm Depth: 5,1 cm Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordCable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketI x Ø11mmDiameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlI x button cell 3.0 V CR2025 lithium manganese built-inLegal specificationsSpecial product:Special product:Not designed for household room illumination	Beam angle (1/10 peak):	31°
Display type:4 digit 7-segment LED displayMaterial:PlasticDimensions:Width: 15 cm Depth: 5,1 cm Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordCable construction:Cable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:Diameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlLegal specificationsSpecial product:Not designed for household room illumination	Housing color:	Black
Material: Plastic Dimensions: Width: 15 cm Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:	Attachment system:	Double bracket
Dimensions:Width: 15 cm Depth: 5,1 cm Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordClass 0 (no noise at all)Cable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:Diameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlI x button cell 3.0 V CR2025 lithium manganese built-inLegal specificationsSpecial product:Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Depth: 5,1 cm Height: 15 cm Weight: 0,75 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Legal specifications Special product: Not designed for household room illumination	Material:	Plastic
Height: 15 cmWeight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordCable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlBattery:1 x button cell 3.0 V CR2025 lithium manganese built-inLegal specificationsSpecial product:Not designed for household room illumination	Dimensions:	Width: 15 cm
Weight:0,75 kgNoise classification:Class 0 (no noise at all)Power cordCable construction:2 x 0,75 mm² H05VVH2-FCable length:Approx. 1,1 mMounting bracketDiameter mounting holes:1 x Ø11mmMaterial:Metal, 1,4 mmRemote controlBattery:1 x button cell 3.0 V CR2025 lithium manganese built-inLegal specificationsSpecial product:Not designed for household room illumination		
Noise classification: Class 0 (no noise at all) Power cord	Weight:	
Power cord Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Diameter mounting holes: Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control I x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination		
Cable construction: 2 x 0,75 mm² H05VVH2-F Cable length: Approx. 1,1 m Mounting bracket Imm Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Imm Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:		
Cable length: Approx. 1,1 m Mounting bracket Ix Ø11mm Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Ix button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:		2 x 0.75 mm2 H05\/\/H2 E
Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product:		
Diameter mounting holes: 1 x Ø11mm Material: Metal, 1,4 mm Remote control Image: Second s		Αρριοχ. 1,1 11
Material: Metal, 1,4 mm Remote control		1 x Ø11mm
Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination		
Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination		
Special product: Not designed for household room illumination		
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting