eurolite®

EUROLITE AKKU Mini PARty RGBW Spot MK2

DMX spotlight with 12 x 1 W LED in the colors red, green, blue and white

Art. No.: 42110205 GTIN: 4026397695489











List price: 59.38 €

incl. 19% VAT.

Features:

Compact design

- Charging and operation also possible via USB power bank
- Battery operation up to 4h
- 12 powerful LEDs 1 W high-power R/G/B/W (homogenous color mix)
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 7°
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Party room; mobile use; small rental
- Cordless, flexible and versatile
- Preprogrammed in Light Captain; Light'J; Colorchief
- Application possibility: Standing; suspended; on stand
- Package contents
- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x USB cable, 1 x remote control, 1 x battery, 2 x mounting bracket, 2 x washer, 2 x knurled screw

Logistic

EAN / GTIN: 4026397695489 Weight: 0,68 kg Length: 0.15 m Width: 0.13 m Heigth: 0.12 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	5V DC
Power consumption:	5 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
Battery pack type:	1 x lithium ion 3,7 V, 2600 mAh, 9,62 Wh
Battery pack:	Battery operation up to 4h Recharging time 4h
Lamp type:	LED lamp
LED type:	12 x 1 W high-power R/G/B/W (homogenous color mix)
DMX channels:	4; 6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	22°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15 cm Depth: 9 cm Height: 15 cm
Weight:	0,61 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting