eurolite®

EUROLITE LED Strip 300 5m 3528 3000K 24V Constant Current

Flexible LED strip with a CRI >90 and 24 V constant current

Art. No.: 50530105 GTIN: 4026397631128





List price: 71.28 €

incl. 19% VAT.

Features:

- Flexible LED strip for decorative lighting
- Constant current technology for high efficiency, durability and homogeneous light distribution
- Greater lengths do not lead to light fall-off and do not require multiple feeders
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- Dimmable
- 300 powerful LEDs SMD 3528 warm white (WW)
- Control via accessory
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
- Package contents
- 1 x device, 1 x user manual

Technical specifications:

Power supply:	24V AC 1000 mA
Power consumption:	23 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397631128 Weight: 0,10 kg Length: 0.02 m Width: 0.02 m Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	300 x SMD 3528 warm white (WW)
Control:	Accessory
Standing/fixation:	Self adhesive
Color temperature:	3000K
Color rendering index (CRI):	91 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	4,5 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	10 cm
Luminous flux (Lumen) per meter:	420 lm/m
Housing color:	White
Dimensions:	Length: 500 cm
	Width: 0,8 cm
	Height: 0,2 cm
Weight:	0,09 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1425968