# eurolite®

## EUROLITE LC-4 LED Strip RGB DMX Controller

3-channel LED controller with DMX interface for RGB LEDs 12-24 V

Art. No.: 50530595 GTIN: 4026397615203



## List price: 39.15 €

incl. 19% VAT.

#### Features:

- Compact LED controller for controlling RGB LEDs (12-24 V) via DMX
- Converts standard DMX512 signals to PWM signals e.g. for driving LED strips
- 3 separate control channels for individual color mixing of red, green and blue LEDs
- Plug-in screw terminals for connecting the LEDs and the power supply
- Rugged black metal housing
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels

## Silent operation Package contents

- 1 x controller, 1 x user manual

#### **Technical specifications:**

Power supply:	12/24V DC
Power consumption:	Max. 108 W 12 V DC
	Max. 216 W 24 V DC
	36 W 12 V DC per channal
	72 W 24 V DC per channal
IP classification:	IP20
Protection class:	Protection class III

#### Logistic

EAN / GTIN: 4026397615203 Weight: 0,16 kg Length: 0.11 m Width: 0.05 m Heigth: 0.03 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Output current:	Max. 3 x 3 A per channal
Power connection:	Via screw terminal
Power output:	Screw terminal
DMX channels:	4
DMX input:	Screw terminal
Cooling:	Passive convection cooling
Control:	DMX; stand-alone
Housing color:	Black matte
Dimensions:	Width: 4,5 cm
	Depth: 10,9 cm
	Height: 2,7 cm
Weight:	0,15 kg
Noise classification:	Class 0 (no noise at all)