eurolite®

EUROLITE LED Strip RGBW 4-channel DMX Controller

4-channel LED controller with DMX interface for RGB LEDs 12-24 V

Art. No.: 50531100 GTIN: 4026397637441



List price: 53.43 €

incl. 19% VAT.

Features:

- Compact LED controller for controlling RGBW LEDs (12-24 V) via DMX
- Converts standard DMX512 signals to PWM signals e.g. for driving LED strips
- 4 separate control channels for individual color mixing of red, green, blue and white LEDs
- Switchable termination resistor
- Plug-in screw terminals for connecting the LEDs and the power supply
- RJ45 jacks for serial connection
- Rugged black metal housing
- Integrated show programs
- Control via stand-alone
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels
- Silent operation
- Package contents
- 1 x device, 1 x user manual

Technical specifications:

12/24V DC
Max. 384 W 12 V DC
Max. 768 W 24 V DC
Max. 96 W 12 V DC per channal
Max. 192 W 24 V DC per channal
Max. 4 x 8 A per channal

Logistic

EAN / GTIN: 4026397637441 Weight: 0,33 kg Length: 0.18 m Width: 0.08 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Via screw terminal
Power output:	Screw terminal
DMX channels:	4
DMX input:	3-pin XLR (M) mounting version 1 x RJ-45 (F) mounting version
DMX output:	3-pin XLR (F) mounting version RJ-45 (F) mounting version
Control:	Stand-alone
Dimensions:	Length: 16,4 cm Width: 6,6 cm Height: 3,8 cm
Weight:	0,30 kg
Noise classification:	Class 0 (no noise at all)