eurolite®

EUROLITE Color Changer Set + PAR-36-pinspot

For starters

Art. No.: 50800530

GTIN: 4026397382242











List price: 59.38 €

incl. 19% VAT.

Features:

- Color-wheel with motor for T-36
- Spot and motor delivered with installed power cord and safety plug
- Use with alternative illuminants having differing beam angles (flood) is possible color wheel
- Color wheel with red, green, yellow, blue illuminant
- Dimmable
- Hot restrike
- Very high color rendering index (CRI) spotlight
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- motor for color wheel
- Control via plug and play
- Package contents
- 1 x spotlight, 1 x illuminant, 1 x motor for color wheel, 2 x nut, 1 x color wheel, 1 x safety bond, 1 x chain link, 1 x lamp clamping ring, 1 x user manual

Technical specifications:		
Weight:	1,55 kg	
Spotlight		
Power supply:	230 V AC, 50 Hz	

Logistic

EAN / GTIN: 4026397382242 Weight: 1,80 kg Length: 0.24 m Width: 0.14 m Heigth: 0.25 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	Max. 30 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 6,4 V/30 W PAR-36 G-53 STC
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 0,9 m
Base:	Wires
Cooling:	Passive convection cooling
Control:	Plug and play
Housing color:	Black
Attachment system:	Mounting bracket
Output:	6.4V AC;
Dimensions:	Length: 16 cm
	Width: 15,5 cm
	Height: 17 cm
Weight:	1 kg
Mounting bracket	
Diameter mounting holes:	3 x Ø10mm; 1 x Ø8mm
Material:	Metal, 2 mm
Illuminant	
Voltage (lamps):	6,4 V
Nominal wattage:	30 W
Base:	G-53 STC
Lamp type:	Halogen lamp; clear lamp
Lamp specification:	Dimmable Hot restrike
Beam angle (1/2 peak):	6°
Color of light:	Warm white WW <3300 K
Color rendering index (CRI):	99 Ra
Energy efficiency class (A - G):	G
Motor for color wheel	
Power supply:	230 V AC, 50 Hz
Power consumption:	4 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 0,9 m
Speed:	2,5 RPM
Control:	Plug and play
Maximum load:	1 kg
Housing color:	Black
Dimensions:	Length: 10 cm Height: 7,5 cm

Weight:	0,3 kg
Color wheel	
Color generation:	Color wheel with red, green, yellow, blue
Diameter mounting holes:	1 x Ø8mm
Material:	Plastic
Dimensions:	Width: 0,2 cm Diameter: Ø 23 cm
Lamp clamping ring	
Material:	Metal
Color:	Silver