

EUROLITE Dynamic Fog 2000 Fog Machine

2000 watt fogger with DMX

Art. No.: 51702050

GTIN: 4026397549218



The article is no longer in our assortment.

Features:

- Concentrated and steady fog output
- Ideal for accentuating light and laser beams
- Adjustable timer with interval, duration and output volume
- Continuous output
- Fan grille with blue LED illumination, switchable
- Short warm-up time
- Output distance: Approx. 5 m
- Control via DMX; wireless remote control; wired remote control; timer
- With mounting bracket
- For application areas such as: Clubs/dancing school; stage; theater; rental
- Big tank capacity
- With level indication
- Operates on water-based fluid
- Preprogrammed in Light Captain
- Removable tank
- Application possibility: Standing; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 2 x remote control, 1 x declaration of conformity, 1 x battery, 1 x container, 1 x filter, 1 x mounting bracket, 2 x screw, 2 x washer, 2 x knurled screw

Logistic

EAN / GTIN: 4026397549218

Weight: 12,55 kg

Length: 0.65 m

Width: 0.39 m

Height: 0.34 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 2000 W

IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 4 min
Output volume:	Approx. 566 m ³ /min
Output distance:	Approx. 5 m
Tank capacity:	5 l water-based fluid removable tank
Fluid consumption:	Approx. 50 ml/min
DMX channels:	1
DMX input:	1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Control:	DMX; wireless remote control; wired remote control; timer
Preprogrammed in:	Light Captain
Housing color:	Black
Attachment system:	Mounting bracket
Controls:	Low fluid; overheat
Color:	Black
Dimensions:	Width: 36 cm Depth: 52 cm Height: 37 cm
Weight:	10,95 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Remote control	
Battery:	1 x 12 V LR27 alkaline manganese built-in
Carrier frequency:	433,920 MHz