

## EUROLITE LED Laser Slim FX Spot

Flat PAR spotlight with additional RG laser (2M) and strobe

Art. No.: 51741074

GTIN: 4026397620801



**The article is no longer in our assortment.**

### Features:

- 6 high-power 4 W 4in1 LEDs for RGBW wash effects
- 12 cold white 0.5 W SMD LEDs for fast, dynamic strobe effects
- 2 laser diodes project thousands of red and green laser beams
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- Spotlight, laser and strobe can be controlled individually
- Auto, music, master/slave and DMX mode
- Silent operation
- 7 built-in auto and music show programs
- Direct color selection for 20 preset colors
- Stepless color mixture, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Sound-control via built-in microphone with adjustable microphone sensitivity
- DMX512 control possible via any commercial DMX controller
- 2, 3, 4, 6, 10, or 14 DMX channels selectable for various applications
- Swivel mounting bracket
- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- 12 powerful LEDs 0,5 W SMD 5050 cold white (CW)
- 6 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone

### Logistic

EAN / GTIN: 4026397620801  
Weight: 2,07 kg  
Length: 0.30 m  
Width: 0.28 m  
Height: 0.16 m

- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 25°

**Package contents**

- 1 x remote control

**Technical specifications:**

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz   |
| Power consumption:     | 60 W   |
| IP classification:     | IP20   |
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:          | 1 x IEC connector (F) mounting version   |
| Lamp type:             | LED lamp   |
| LED type:              | 12 x 0,5 W SMD 5050 cold white (CW)<br>6 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)   |
| Flash rate:            | 0 - 20 Hz  |
| Laser class:           | 2M   |
| Laser color:           | R/G  |
| Laser module:          | Green (G) 50 mW 532nm<br>Red (R) 100 mW 650nm  |
| DMX channels:          | 2; 3; 4; 6; 10; 14   |
| Cooling:               | Cooling fan  |
| Control:               | Stand-alone; DMX; IR remote control; sound to light via microphone                               |
| Preprogrammed in:      | Light´J; LED PC-Control 512; Light Captain   |
| Beam angle:            | 25°  |
| Beam angle (1/2 peak): | 25°  |
| Housing color:         | Black  |
| Dimensions:            | Width: 26,5 cm<br>Depth: 10 cm<br>Height: 21 cm  |
| Weight:                | 1,73 kg  |
| Remote control         |  |
| Battery:               | 1 x button cell 3.0 V CR2025 lithium manganese built-in  |
| LEDs                   |  |
| Wash effect:           | 6 x RGBW (4in1), 4 W each  |
| Strobe effect:         | 12 x white, 0.5 W each   |
| DMX connection:        | 3-pin XLR  |
| Legal specifications   |  |
| Special product:       | Not designed for household room illumination   |
| Intended use:          | Show effect lighting   |