
# eurolite®

## EUROLITE LED Laser Derby MK2

DMX light effect with RG laser (2M), rotating LED derby, stroboscope and IR remote control

Art. No.: 51741079 GTIN: 4026397690019











## List price: 224.91 €

incl. 19% VAT.

#### Features:

- 2 laser diodes project hundreds of red and green laser beams
- 7 integrated show programs
- Dimmer electronic; color macros adjustable

 Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)

- The device is cooled by cooling fan
- With mounting bracket
- 4 digit 7-segment LED display
- Laser; multi beam effect; strobe effect
- Preprogrammed in Light Captain; EASY SHOW 2; Colorchief
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Application possibility: Suspended; on stand laser
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer

#### light effect

- 4 powerful LEDs 10 W SMD 5050 R/G/B/W
- strobes
- 16 powerful LEDs 0,6 W SMD 2835 cold white (CW)

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x mounting bracket, 2 x knurled screw, 2 x washer

#### Logistic

EAN / GTIN: 4026397690019 Weight: 2,50 kg Length: 0.31 m Width: 0.27 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug
Power output:	IEC connector (F) mounting version Bypass
Fuse:	5 x 20 mm, T 1,6 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	2; 4; 5; 6; 8; 7; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W- DMX by wireless solution via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; Colorchief
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Control elements:	Navigation keys, sensitivity rotary dial
Status LED:	DMX, slave mode, auto mode, sound mode
Dimensions:	Width: 26 cm Depth: 19 cm Height: 19 cm
Weight:	2,17 kg
Power cord	
Cable length:	1,5 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 35 mW 515nm Red (R) 100 mW 650nm
Light effect	
LED type:	4 x 10 W SMD 5050 R/G/B/W
Strobes	
LED type:	16 x 0,6 W SMD 2835 cold white (CW)