eurolite®

EUROLITE LED FE-1500 Hybrid Laser Flower

Bright effect with derby, laser (class 2M) and stroboscope

Art. No.: 51741080 GTIN: 4026397532302



The article is no longer in our assortment.

Features:

- 3-in-1 DMX light effect with red and green laser diodes, rotating LED derby and white strobe LEDs
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- 2 laser diodes project thousands of red and green laser beams
- Rotating derby for mirror ball effects with five 3 W LEDs (red, green, blue, white and amber)
- Eight white 1 W strobe LEDs
- Auto, music, master/slave and DMX mode
- 7 built-in auto and music show programs
- Addressing and setting via control panel with 4-digit LED display
- Sound-control via built-in microphone with sensitivity control
- Mounting bracket for flexible wall mounting and ceiling suspension
- When fog is used, this effect becomes especially attractive
- Switch-mode power supply for operation between 100 and 240 Volts
- Feed-through output allows to power up to 8 devices
- 8 powerful LEDs 1 W high-power cold white (CW) (homogenous color mix)
- 5 powerful LEDs 3 W high-power R/G/B/W/A
- Multi beam effect; flower effect; strobe effect
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With a beam angle of 17°

Logistic

EAN / GTIN: 4026397532302 Weight: 5,10 kg Length: 0.35 m Width: 0.29 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.









Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	8 x 1 W high-power cold white (CW) (homogenous color mix)
	5 x 3 W high-power R/G/B/W/A
Flash rate:	0 - 30 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 50 mW 532nm Red (R) 100 mW 650nm
DMX channels:	9
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	Black
Dimensions:	Width: 24,6 cm
	Depth: 31,5 cm
	Height: 31,3 cm
Weight:	4,55 kg
Color LEDs:	5 x RGBWA, 3 W each
Strobe LEDs:	8 x white, 1 W each
DMX connection:	3-pin XLR