eurolite®

EUROLITE LED TMH-41 Hypno Moving Head Spot

Narrow angled spotlight with 3 hypno rings, 30 W LED, gobo and color wheel

Art. No.: 51785895 GTIN: 4026397592764











List price: 534.31 €

incl. 19% VAT.

Features:

- Compact lightweight
- 76 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
 segments controlled separately
- 1 powerful LED 30 W COB (chip-on-board) color wheel
- Positioning within 540° PAN, 210° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual
- Gobo effect; beam effect
- Gobo wheel with static gobos, 9 gobos and open
shake effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 4,7°
- 4 digit 7-segment LED display
- Dimmer electronic; color blend stepless
- Color wheel with 9 dichroic filters plus open
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- DMX feed-through for up to 32 further DMX devices
- DMX fail mode (hold; sound; auto; zero values)
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended Package contents

Logistic

EAN / GTIN: 4026397592764 Weight: 6,60 kg Length: 0.44 m Width: 0.27 m Heigth: 0.34 m - 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable, 2 x screw, 2 x washer

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	76 x SMD 5050 3in1 TCL RGB (homogenous color mix)
	1 x 30 W COB (chip-on-board) color wheel
Max. TILT movement:	210° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 25 Hz
Equipment:	Gobo wheel with static gobos; focus manual
Color generation:	Color wheel with 9 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 9 gobos and oper Shake effect
DMX channels:	12; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
DMX features:	DMX feed-through for up to 32 further DMX devices
DMX fail mode:	Hold; sound; auto; zero values
Beam angle:	4,7°
Beam angle (1/2 peak):	4,7°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24,5 cm
	Depth: 16,5 cm
	Height: 35 cm 5,68 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	Not designed for beyeshold room illumination
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting