

EUROLITE LED TMH FE-300 Beam/Flower Effect

Handy RGBW moving head flower with rotating lens and 12 W LEDs

Art. No.: 51785954

GTIN: 4026397556421



The article is no longer in our assortment.

Features:

- Equipped with 3 x 12 W COB LED in the colors red, green, blue and white
- 11 or 17 DMX channels selectable
- Compact lightweight
- Functions: colored beams in R, G, B and W, color change with diverse settings, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Adjustable zoom movement - from narrow single beam to room-filling beams - via rotating lens
- Stepless RGBW color mixture
- Strobe effect with 1-18 flashes per second
- Exact positioning via 16 bit PAN/TILT movement resolution
- Positioning within 540° PAN and 190° TILT
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with 4-digit LED display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- DMX control via every standard DMX controller
- 3 powerful LEDs 12 W COB (chip-on-board) 4in1 QCL RGBW
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect; beam effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 6,5°

Logistic

EAN / GTIN: 4026397556421
Weight: 4,52 kg
Length: 0.28 m
Width: 0.24 m
Height: 0.36 m

Package contents

- 1 x omega bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	3 x 12 W COB (chip-on-board) 4in1 QCL RGBW
Max. TILT movement:	190° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
DMX channels:	11; 17
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	6,5°
Beam angle (1/2 peak):	6,5°
Housing color:	Black
Dimensions:	Width: 20 cm Depth: 14,5 cm Height: 28 cm
Weight:	3,93 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting