eurolite®

EUROLITE LED TMH-S30 Moving Head Spot

Compact moving head Spot with 30 W LED, gobos and color wheel

Art. No.: 51786070 GTIN: 4026397673777











List price: 343.91 €

incl. 19% VAT.

Features:

- 1 powerful LED 30 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 170° TILT
- Exact positioning (16 bit resolution)
- Color wheel; focus manual; gobo wheel with rotating gobos
- Beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Flicker-free
- With a beam angle of 8°
- 4 digit 7-segment LED display
- Dimmer electronic
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended Package contents

Logistic

EAN / GTIN: 4026397673777 Weight: 3,45 kg Length: 0.29 m Width: 0.22 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. - 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz	
Power consumption:	45 W	
IP classification:	IP20	
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)	
Fuse:	T 1 A fuse replaceable	
Lamp type:	LED lamp	
LED type:	1 x 30 W COB (chip-on-board) cold white (CW)	
Max. TILT movement:	170° exact positioning (16 bit resolution)	
Max. PAN movement:	540° exact positioning (16 bit resolution)	
Equipment:	Color wheel; focus manual; gobo wheel with rotating gobos	
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions	
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 14mm Image diameter 10mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement	
DMX channels:	10; 12	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	Cooling fan	
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)	
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3	
Projection:	Flicker-free	
Beam angle:	8°	
Beam angle (1/2 peak):	8°	
Color temperature:	8000K	
Illuminance in Lux (lx):	Cold white (CW) 1m: 14450 lx, 3m: 1574 lx, 6m: 377 lx	
Housing color:	Black	
Display type:	4 digit 7-segment LED display	
Transport aid:	Rubber feet	
Dimensions:	Width: 17,0 cm Depth: 15,0 cm Height: 24,0 cm	

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting