

EUROLITE LED TMH-B60 Moving Head Beam

Moving moving head with 60 W COB LED in RGBW

Art. No.: 51786082

GTIN: 4026397710472



List price: 296.31 €

incl. 19% VAT.

Features:

- Compact lightweight
 - 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
 - Positioning within 540° PAN, 180° TILT
 - Beam effect; strobe effect
 - 4 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
 - Flicker-free
 - With a beam angle of 2°
 - 4 digit 7-segment LED display
 - Rubber feet
 - Dimmer electronic; Motion macros adjustable
 - Preprogrammed in Light Captain
 - For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
 - Application possibility: Standing; suspended
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397710472

Weight: 3,65 kg

Length: 0.29 m

Width: 0.22 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|--------------------------|---|
| Power consumption: | 60 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Fuse: | 5 x 20 mm, T 1,5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 180° positioning |
| Max. PAN movement: | 540° positioning |
| DMX channels: | 12; 14 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 2° |
| Beam angle (1/2 peak): | 2° |
| Beam angle (1/10 peak): | 5° |
| Illuminance in Lux (lx): | Red (R) 1m: 19079 lx, 3m: 3275 lx, 6m: 838 lx Green (G) 1m: 34129 lx, 3m: 5358 lx, 6m: 1372 lx Blue (B) 1m: 3925 lx, 3m: 1084 lx, 6m: 277 lx Cold white (CW) 1m: 48589 lx, 3m: 8089 lx, 6m: 2048 lx All 3m: 17330 lx, 6m: 4405 lx |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 17,5 cm Depth: 15,0 cm Height: 25,0 cm |
| Weight: | 3,25 kg |