

EUROLITE LED TMH-S180 Moving Head Spot

LED moving head spot with 200 W LED, rotating gobos, color wheel, prism and QuickDMX port

Art. No.: 51786086

GTIN: 4026397702521



List price: 950.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold rotating; focus motor-driven
- Multi beam effect; gobo effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
- Flicker-free
- With a beam angle of 10°
- LCD display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397702521

Weight: 12,80 kg

Length: 0.53 m

Width: 0.44 m

Height: 0.31 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Gobo wheel with rotating gobos; prism 3-fold rotating; focus motor-driven
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 23,5mm Image diameter 15mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	13; 15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10°
Illuminance in Lux (lx):	Cold white (CW) 3m: 20700 lx, 6m: 5273 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 32,5 cm Depth: 27,0 cm Height: 45,5 cm

Weight:	11,35 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting