eurolite®

EUROLITE LED TSL-250 Scan COB

Handy scanner with 30 W COB LED, gobo and color wheel

Art. No.: 51786125 GTIN: 4026397685138











List price: 296.31 €

incl. 19% VAT.

Features:

- Compact design
- 1 powerful LED 30 W COB (chip-on-board)
- Positioning within TILT
- Color wheel; gobo wheel with rotating gobos; focus manual
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 9°
- LCD display
- Dimmer electronic
- Preprogrammed in Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x mounting bracket, 2 x screw

Logistic

EAN / GTIN: 4026397685138 Weight: 3,75 kg Length: 0.41 m Width: 0.23 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board)
Equipment:	Color wheel; gobo wheel with rotating gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open
	Outside diameter 14mm
	Image diameter 10mm Gobos changeable
	Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB
Preprogrammed in:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY
Preprogrammed in: Projection:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Preprogrammed in: Projection: Beam angle:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak):	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9°
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak): Illuminance in Lux (lx):	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9° 9° 0 Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 145
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak): Illuminance in Lux (lx): Housing color:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9° 9° 20 Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 148 lx
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak): Illuminance in Lux (lx):	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9° 9° Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 148 lx Black
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak): Illuminance in Lux (lx): Housing color: Display type:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light 'J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9° 9° Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 148 lx Black LCD display Rubber feet Width: 16,0 cm Depth: 15,0 cm
Preprogrammed in: Projection: Beam angle: Beam angle (1/2 peak): Illuminance in Lux (lx): Housing color: Display type: Transport aid:	to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 Flicker-free 9° 9° Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 145 lx Black LCD display Rubber feet Width: 16,0 cm

Intended use:

Show effect lighting