# eurolite®

## **EUROLITE LED TSL-750 Scan**

Scanner with 75 W LED, gobos, rotating prism, color wheel, motorized focus

Art. No.: 51786185 GTIN: 4026397543377











# The article is no longer in our assortment.

#### Features:

- Equipped with a 75 W LED
- 13 or 15 DMX channel mode selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Internal programs
- Color wheel with 8 dichroic color filters and white
- Rainbow effect with adjustable speed
- Gobo-wheel with 7 rotating gobos plus open
- Gobo shake function
- Rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer
- Lightbeam with 14° radiation angle
- Control board with graphic LC display and four operating buttons for adjusting the DMX starting address, PAN/TILT reverse
- Switch-mode power supply for operation between 100 and 240 Volts
- DMX control via every standard DMX controller
- 1 powerful LED 75 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Gobos
- Gobo effect
- Color wheel with 8 dichroic filters plus open
- Gobo wheel with rotating gobos, 7 gobos and open
- The device is cooled by cooling fan

### Logistic

EAN / GTIN: 4026397543377 Weight: 8,35 kg Length: 0.59 m Width: 0.36 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	80° exact positioning (16 bit resolution)
Max. PAN movement:	175° exact positioning (16 bit resolution)
Flash rate:	0 - 18 Hz
Equipment:	Gobos
Color generation:	Color wheel with 8 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open
DMX channels:	13; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	14°
Beam angle (1/2 peak):	14°
Housing color:	Black
Dimensions:	Width: 26 cm Depth: 47,5 cm Height: 22,5 cm
Weight:	6,95 kg
Legal specifications	
Special product:	Not designed for household room illumination