

EUROLITE LED TSL-1200 Scan

Scanner with 120 W LED, gobos, rotating prism, color wheel, motorized focus

Art. No.: 51786190 GTIN: 4026397556506











The article is no longer in our assortment.

Features:

- Equipped with a 120 W COB LED
- 13 or 15 DMX channel mode selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Internal programs
- Color wheel with 8 dichroic color filters and white
- Rainbow effect with adjustable speed
- Gobo-wheel with 7 rotating gobos plus open
- Gobo shake function
- Rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer
- Lightbeam with 14° radiation angle
- Control board with graphic LC display and four operating buttons for adjusting the DMX starting address, PAN/TILT reverse
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Gobo effect
- Color wheel with 8 dichroic filters plus open
- Gobo wheel with rotating gobos, 7 gobos and open
- The device is cooled by cooling fan

Logistic

EAN / GTIN: 4026397556506

Weight: 9,10 kg Length: 0.55 m Width: 0.26 m Heigth: 0.24 m

- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|------------------------|--|
| Power consumption: | 165 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED type: | 1 x 120 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 80° exact positioning (16 bit resolution) |
| Max. PAN movement: | 175° exact positioning (16 bit resolution) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven |
| Color generation: | Color wheel with 8 dichroic filters plus open |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open |
| DMX channels: | 13; 15 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; stand-alone; sound to light via microphone |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 14° |
| Beam angle (1/2 peak): | 14° |
| Housing color: | Black |
| Dimensions: | Width: 26 cm |
| | Depth: 47,5 cm |
| | Height: 22,5 cm |
| Weight: | 8,45 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |