

EUROLITE LED Twin Scan Bar

LED Scan Bar with 2 full-fledged scanners, incl. IR remote control

Art. No.: 51786200

GTIN: 4026397708127



List price: 581.91 €

incl. 19% VAT.

Features:

- 2 powerful LEDs 37,5 W COB (chip-on-board) cold white (CW) moving lights effects controlled separately
- Positioning within TILT
- Gobo wheel with static gobos; color wheel
- Color wheel with 7 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open
- 16 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; IR remote control; rotary dial for microphone sensitivity; rotary dial for brightness; DMX; QuickDMX (optional); WDMX by wireless solution (optional); CRMX by LumenRadio (optional)
- The article is delivered pre-assembled
- With a beam angle of 12°
- Multicolor OLED display
- For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
- Color selection; Dimmer electronic
- Strobe effect
- With omega bracket
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- Application possibility: On stand; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x remote control, 1 x battery, 1 x bag

Logistic

EAN / GTIN: 4026397708127

Weight: 6,85 kg

Length: 0.66 m

Width: 0.16 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Device fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	2 x 37,5 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with static gobos; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	2; 5; 7; 8; 14
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	2 x temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control; rotary dial for microphone sensitivity; rotary dial for brightness; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Beam angle:	12°
Beam angle (1/2 peak):	12°
Color temperature:	8500K
Housing color:	Black
Attachment system:	Omega bracket Ø 35mm
Display type:	Multicolor OLED display
Dimensions:	Length: 60 cm Width: 11,8 cm Height: 28,5 cm
Weight:	6,25 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in