

# FUTURELIGHT Profile 200, 20-45°

PRO profile spotlight, warm white 200 W LED, zoom, CRI >90, extremely quiet

Art. No.: 51840915

GTIN: 4026397625714





List price: 1188.81 €

incl. 19% VAT.

#### Features:

- Glass front lens
- 1 powerful LED 200 W COB (chip-on-board) warm white (WW)
- Focus manual; zoom manual
- Strobe effect
- The device is cooled by low-noise cooling fan
- Control via DMX
- Flicker-free
- With a beam angle of 20° 45°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Theater; stage; rental
- Dimmer electronic; Dimmer speed (step response) adjustable
- Preprogrammed in LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Application possibility: Suspended; on stand

## Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame, 1 x holder, 1 x XLR cable, 1 x plug (male)

### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W

## Logistic

EAN / GTIN: 4026397625714

Weight: 12,80 kg Length: 0.80 m Width: 0.32 m Heigth: 0.33 m

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Equipment:	Focus manual; zoom manual
Gobos:	Outside diameter 85mm Image diameter 60mm
DMX channels:	1; 2
DMX input:	1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	DMX
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	20° - 45°
Beam angle (1/2 peak):	20 - 45°
Beam angle (1/10 peak):	20 - 45°
Color rendering index (CRI):	97 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 64,5 cm Width: 27,6 cm Height: 27,7 cm
Weight:	10,90 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting