

FUTURELIGHT EYE-7.i LED Moving Head Beam

4in1 moving head beam with unlimited PAN and TILT movement

Art. No.: 51841306

GTIN: 4026397513509



The article is no longer in our assortment.

Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed and Infinity function (.i) for unlimited PAN and TILT movement
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 7 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Beam effect
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397513509

Weight: 7,95 kg

Length: 0.46 m

Width: 0.32 m

Height: 0.27 m

- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 7°

Package contents

- 1 x omega bracket

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 110,00 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 7 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | Exact positioning (16 bit resolution) plus infinity auto position correction (feedback) |
| Max. PAN movement: | Exact positioning (16 bit resolution) plus infinity auto position correction (feedback) |
| Flash rate: | 0 - 18 Hz |
| DMX channels: | 14; 15; 16; 22 |
| DMX input: | 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone |
| Preprogrammed in: | LED PC-Control 512 |
| Beam angle: | 7° |
| Beam angle (1/2 peak): | 7° |
| Beam angle (1/10 peak): | 12° |
| Illuminance in Lux (lx): | Red (R) 3m: 2714 lx, 6m: 611 lx Green (G) 3m: 4900 lx, 6m: 1161 lx Blue (B) 3m: 830 lx, 6m: 199 lx Cold white (CW) 3m: 5539 lx, 6m: 1294 lx All 3m: 12673 lx, 6m: 2948 lx |
| Housing color: | Black |
| Dimensions: | Width: 24,4 cm Depth: 17,9 cm Height: 35 cm |
| Weight: | 6,80 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |