

FUTURELIGHT EYE-37 RGBW Zoom LED Moving Head Wash

PRO washlight with RGBW color mixing, very large zoom range and Art-Net

Art. No.: 51841314

GTIN: 4026397629507



The article is no longer in our assortment.

Features:

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 37 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- Positioning within 540° PAN, 265° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; Art-Net; stand-alone; sound to light via microphone; master/slave function; W-DMX by wireless solution upgradeable
- Flicker-free
- With a beam angle of 2° - 50°
- Dimmer electronic; color blend stepless; colors preset
- Strobe effect
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x declaration of conformity, 1 x mounting bracket

Logistic

EAN / GTIN: 4026397629507

Weight: 22,25 kg

Length: 0.71 m

Width: 0.51 m

Height: 0.34 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 530 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED type: | 37 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 265° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 30 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 18; 19; 20; 41; 170 |
| DMX input: | 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 5-pin XLR (F) mounting version |
| Network connection: | Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; Art-Net; stand-alone; sound to light via microphone; master/slave function; W-DMX by wireless solution upgradeable |
| Preprogrammed in: | Light J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 2° - 50° |
| Beam angle (1/2 peak): | 2 - 28° |
| Beam angle (1/10 peak): | 8 - 50° |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 5874 lx, 6m: 1655 lx Wide red (R) 3m: 564 lx, 6m: 146 lx Narrow green (G) 3m: 11065 lx, 6m: 3219 lx Wide green (G) 3m: 1160 lx, 6m: 305 lx Narrow blue (B) 3m: 1666 lx, 6m: 563 lx Wide blue (B) 3m: 202 lx, 6m: 54 lx Narrow cold white (CW) 3m: 15461 lx, 6m: 4527 lx Wide cold white (CW) 3m: 1545 lx, 6m: 408 lx Narrow all 3m: 31814 lx, 6m: 9366 lx Wide all 3m: 3266 lx, 6m: 859 lx |
| Housing color: | Black |
| Dimensions: | Width: 44,4 cm Depth: 25 cm Height: 57 cm |
| Weight: | 19,00 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |