

# FUTURELIGHT DMH-75.i LED Spot

High performance LED moving head with 72 W LED and unlimited PAN and TILT movement

Art. No.: 51841840 GTIN: 4026397513097



## The article is no longer in our assortment.

#### Features:

- 1 extra bright 72 W LED for best luminance
- High PAN/TILT speed and Infinity function (.i) for unlimited PAN and TILT movement
- 12, 14, 16 or 18 DMX channels selectable
- Beam angle between 13° and 18° adjustable
- Effect wheel with rotating 3-facet prism
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- Sound-controlled via built-in microphone
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Number of scenes can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- Switch-mode power supply for operation between 100 and 240 Volts

### Logistic

EAN / GTIN: 4026397513097 Weight: 11,55 kg Length: 0.58 m Width: 0.38 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- Control via sound to light via microphone; DMX; RDM
- Preprogrammed in Light'J
- With a beam angle of 12°

### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	115 W
Gobos:	Outside diameter 24mm Image diameter 19mm
DMX channels:	12
Control:	Sound to light via microphone; DMX; RDM
Preprogrammed in:	Light <sup>′</sup> J
Beam angle:	12°
Beam angle (1/2 peak):	12°
Color:	Black
Dimensions:	Width: 25,2 cm Depth: 29,9 cm Height: 39,8 cm
Weight:	9,90 kg
DMX channels:	12/14/16/18
DMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED number:	1
LED type:	Array 72 W, white
Beam angle:	13° - 18°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	24 mm
Image diameter of the gobos:	19 mm
Maximum PAN-movement:	unlimited
Maximum TILT-movement:	unlimited
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting