

FUTURELIGHT PRO Slim Strobe SMD 840 CW

PRO slimline LED strobe with 840 x cold white (CW) LEDs, 16 separately controllable LED rings and switchable 4683716368





Art. No.: 51842710









incl. 19% VAT.

Features:

- 840 powerful LEDs 0,5 W SMD 5730 cold white (CW)
16 segments controlled separately
- Frost filter electronic
- Strobe effect
- 27 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With mounting bracket
- LCD display
- Silent operation
- Mains input and output for power linking up to 8 units
- Preprogrammed in Light Captain
- For application areas such as: Clubs/dancing school; stage; theater; rental
- Application possibility: Suspended; on stand
- Package contents
- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397716368 Weight: 6,15 kg Length: 0.30 m Width: 0.30 m Heigth: 0.30 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	840 x 0,5 W SMD 5730 cold white (CW)
Flash rate:	1 - 30 Hz
DMX channels:	2; 3; 5; 7; 17; 23
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Color temperature:	6300K
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Width: 30,5 cm Depth: 14,5 cm Height: 34,5 cm
Weight:	5,50 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting