

MADRIX STELLA

USB and Art-Net interface to control two DMX universes with MADRIX

Art. No.: 51860365

GTIN: 4260263421196



List price: on demand €

incl. 19% VAT.

Features:

- Can transmit up to 1024 DMX channels
- The device is cooled by passive convection cooling
- Control via DMX; RDM; Art-Net
- The device can be connected via USB to the PC
- Made in Germany
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels; architecture
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4260263421196

Weight: 0,55 kg

Length: 0.23 m

Width: 0.17 m

Height: 0.07 m

Technical specifications:

Power supply:	5-24V AC
IP classification:	IP20
Power connection:	Mains input via USB, type B power supply cord for USB A mains connection (provided)
DMX channels:	Output 1024
Network connection:	Protocol: Art-Net 1,2,3,4 incl. ArtSync via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s Protocol: Streaming ACN (sACN / ANSI E1.31) via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s
Cooling:	Passive convection cooling

Control:	DMX; RDM; Art-Net
USB port:	USB 2.0, type B
PC connect:	Via USB
Dimensions:	Width: 7 cm Depth: 9,2 cm Height: 4,5 cm
Weight:	0,37 kg