

EUROLITE Stage Panel 32 HCL LED

Light effect bar with RGBAW+UV color mixing, with 5-pin QuickDMX connector

Art. No.: 51913893

GTIN: 4026397628234



The article is no longer in our assortment.

Features:

- 32 high-power 10 W RGBAW+UV LEDs (6in1)
- 8 segments for dynamic running lights
- Built-in auto and music show programs
- Direct color selection for 26 preset colors
- Variable color temperature 2700-8000 K
- Stepless color blend, color change, color fade, dimmer and strobe effect
- 4 barn doors to avoid blinding the audience and for protection during transport
- Control panel with LED display for easy configuration
- Convenient wireless control via included IR remote control
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered socket for QuickDMX receivers (optional)
- Swivel mounting bracket
- Additional bracket for floor use
- Mains input and output for power linking up to 8 units
- 32 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 16°

Package contents

- 1 x remote control

Logistic

EAN / GTIN: 4026397628234

Weight: 10,00 kg

Length: 0.57 m

Width: 0.18 m

Height: 0.40 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	32 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 6; 13; 48; 52
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	35°
Housing color:	Black
Dimensions:	Width: 50 cm Depth: 9,3 cm Height: 29,5 cm
Weight:	8,65 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting