EUROLITE Multiflood Pro IP RGBW Wash/Frost

Bright LED outdoor spot with wireless DMX receiver

eurolite









The article is no longer in our assortment.

Features:

- Washlight and strobe
- Suitable for external use (IP65)
- With integrated wireless receiver for WDMX operation (Wireless Solution made in Sweden)
- 36 high-power 15 W RGBW LEDs (4in1)
- 16° standard beam angle
- 2 frost filters (25° and 45°) for a softer light with larger beam angles, included in delivery
- Flicker-free projection
- Direct color selection for 20 preset colors
- Stepless RGBW color blend
- Dimmer speed (step response) adjustable
- Addressing and setting via control panel with LED screen and four operating buttons
- Swivel mounting bracket with locking possibility
- Hanging installation via quick-lock Omega holders
- Additional rubber feet protect the device when positioned on the ground
- IP T-Con terminals for power linking up to 8 units
- 36 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by cooling fan
- Control via W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand-alone
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 16°
- Suitable for outdoor use IP65
- Package contents
- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x XLR cable, 1 x omega bracket, 2 x frost filter, 1 x plug (male)

Logistic

EAN / GTIN: 4026397658118 Weight: 13,25 kg Length: 0.53 m Width: 0.22 m Heigth: 0.40 m

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--|--|
| Power consumption: | 215 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Lamp type: | LED lamp |
| LED type: | 36 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 4; 5; 8 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Cooling fan |
| Control: | W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand alone |
| Preprogrammed in: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 16° |
| Beam angle (1/2 peak): | 16° |
| | 25° |
| | 45° |
| Beam angle (1/10 peak): | 35° |
| Housing color: | Black |
| Dimensions: | Length: 16 cm |
| | Width: 49 cm |
| | Height: 32 cm |
| Weight: | 12,05 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| | |
| Legal specifications | |
| Legal specifications Special product: | Not designed for household room illumination |