

### **EUROLITE LED IP PAD 9x8W HCL**

Weather-proof DMX spotlight (IP65) with 9 x 8 W 6in1 LED (RGBWA+UV)

Art. No.: 51914159 GTIN: 4026397539776











## The article is no longer in our assortment.

#### Features:

- Equipped with 9 high-power 6in1LEDs in the colors red, green, blue, amber, white and UV
- Functions: static colors, RGBAWUV color mixture, automatic color change, internal programs, dimmer, strobe effect, Master/Slave
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Dimmer speed (step response) adjustable
- For architectural lighting
- Suitable for external use (IP65)
- Compact, matt grey housing
- Infrared remote control included in delivery
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- 9 powerful LEDs 8 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; RDM
- Preprogrammed in EASY SHOW 1; Light'J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 20°
- Suitable for outdoor use IP65
- Silent operation

#### Package contents

1 x remote control

### Logistic

EAN / GTIN: 4026397539776

Weight: 4,75 kg Length: 0.30 m Width: 0.20 m Heigth: 0.31 m

# **Technical specifications:**

- common opcomonation	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	9 x 8 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	2; 3; 4; 5; 6; 7; 8; 9; 10
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; RDM
Preprogrammed in:	EASY SHOW 1; Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	37°
Housing color:	Grey
Dimensions:	Width: 20,5 cm Depth: 12 cm Height: 22,3 cm
Weight:	4,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting