

EUROLITE LED IP PAR 3x8W QCL Spot

Weather-proof (IP65) spotlight with 3 x 8 W LED and 4in1 QCL RGBW color mixing

Art. No.: 51914234

GTIN: 4026397683974



List price: 201.11 €

incl. 19% VAT.

Features:

- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 - Strobe effect
 - Direct color selection for 25 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; IR remote control; DMX
 - Flicker-free
 - With a beam angle of 15°
 - With double bracket
 - LCD display
 - Suitable for outdoor use IP65
 - With pressure compensation membrane
 - Silent operation
 - Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
 - For application areas such as: Installation; stage; rental; architecture
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397683974
Weight: 3,20 kg
Length: 0.19 m
Width: 0.19 m
Height: 0.29 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W

IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse serviceable
Lamp type:	LED lamp
LED type:	3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm
Weight:	3,00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 1,0 mm ² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting