eurolite®

EUROLITE LED IP PAR 9 UV Spot

Weather-proof (IP65) PRO UV spotlight with 9 UV LEDs (365nm), incl. IR remote control

Art. No.: 51914255 GTIN: 4026397697179











List price: 593.81 €

incl. 19% VAT.

Features:

- Minimum visible light
- High output at full intensity
- 9 powerful LEDs 3 W high-power ultra violet (UV)
- UV effect
- 4 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; master/slave function
- With a beam angle of 20°
- With double bracket
- LCD display
- Suitable for outdoor use
- Dimmer electronic
- Preprogrammed in Light Captain; Light J; Colorchief
- For application areas such as: Clubs/dancing school; installation; theater; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand Package contents
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65

Logistic

EAN / GTIN: 4026397697179 Weight: 5,40 kg Length: 0.38 m Width: 0.33 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F)
LED type:	9 x 3 W high-power ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; master/slave function
Preprogrammed in:	Light Captain; Light J; Colorchief
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	50
Wavelength:	370 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28,90 cm
	Depth: 15,25 cm
	Height: 33,80 cm
Weight:	4,87 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm ² H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Remote control Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	Built-III
Special product:	Not designed for household room illumination