eurolite®

EUROLITE LED IP FL-30 COB UV

Weather-proof (IP54) UV spotlight with 30 W COB UV LED

Art. No.: 51914559 GTIN: 4026397506396



0







List price: 141.61 €

incl. 19% VAT.

Features:

- Suitable for larger distances
- 1 powerful LED 30 W COB (chip-on-board) ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 120°
- With mounting bracket
- Suitable for outdoor use IP54
- Silent operation
- For application areas such as: Restaurants, bars and hotels; small rental; architecture; installation
- Application possibility: Suspended Package contents
- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	34 W
IP classification:	IP54
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Logistic

EAN / GTIN: 4026397506396 Weight: 1,45 kg Length: 0.23 m Width: 0.20 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,6 m
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) ultra violet (UV)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	120°
Beam angle (1/2 peak):	120°
Wavelength:	Ultra violet (UV) 395 nm
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 22,5 cm
	Depth: 12,5 cm
	Height: 19,5 cm
Weight:	1,34 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø12mm; 2 x Ø10mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting