# eurolite®

## EUROLITE LED IP FL-10 SMD red

Flat IP65 outdoor floodlight with 20 SMD-LEDs red (R)

Art. No.: 51914901 GTIN: 4026397692860









# List price: 29.63 €

incl. 19% VAT.

### Features:

- 20 powerful LEDs SMD 5730 red (R)
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Suitable for outdoor use IP65
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

#### Package contents

- 1 x spotlight, 1 x user manual

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1 m

#### Logistic

EAN / GTIN: 4026397692860 Weight: 0,48 kg Length: 0.15 m Width: 0.18 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	20 x SMD 5730 red (R)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	80°
Beam angle (1/10 peak):	120°
Color of light:	Red
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 13,4 cm
	Depth: 3,0 cm
	Height: 12,2 cm
Weight:	0,43 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø6mm
Material:	Metal, 2 mm