eurolite®

EUROLITE LED IP FL-50 SMD UV

Flat IP65 outdoor floodlight with 100 SMD-LEDs ultra violet (UV)

Art. No.: 51914996 GTIN: 4026397692754











List price: 153.51 €

incl. 19% VAT.

Features:

- 100 powerful LEDs SMD 5730 ultra violet (UV)
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Suitable for outdoor use IP65
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1 m

Logistic

EAN / GTIN: 4026397692754 Weight: 1,37 kg Length: 0.23 m Width: 0.07 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	100 x SMD 5730 ultra violet (UV)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color of light:	UV-reflecting
Wavelength:	375 nm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 24 cm
	Depth: 4 cm
	Height: 19,5 cm
Weight:	1,27 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting