eurolite®

EUROLITE LED IP FL-10 SMD WW

Flat outdoor floodlight (IP66) with white SMD LEDs





List price: 11.78 €

incl. 19% VAT.

Features:

- 12 powerful LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended
- Package contents
- 1 x device, 1 x user manual

Technical specifications:

230 V AC, 50 Hz
10 W
IP66
Protection class I
Fixed power supply cord with safety plug
3 x 1,0 mm ² H05RN-F
Approx. 1 m

Logistic

EAN / GTIN: 4026397695953 Weight: 0,33 kg Length: 0.13 m Width: 0.07 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	12 x SMD 2835 warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120
Color temperature:	3000K
Color rendering index (CRI):	81 Ra
Luminous flux:	862 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 10,3 cm
	Depth: 2,3 cm
	Height: 10,3 cm
Weight:	0,30 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Energy efficiency class (A - G):	F
EPREL-Nr:	963545
Mounting bracket	
Diameter mounting holes:	1 x Ø8mm; 2 x Ø6mm
Material:	Metal, 1,5 mm