

EUROLITE LED SLS-30 COB UV Floor

Compact UV spotlight with 30 W LED, DMX and remote control

Art. No.: 51915303

GTIN: 4026397669305



List price: 117.81 €

incl. 19% VAT.

Features:

- Striking blacklight effect
 - Strobe effect with adjustable speed
 - DMX and power terminals intelligently designed for easy wiring
 - 1 powerful LED 30 W COB (chip-on-board) ultra violet (UV)
 - UV effect; strobe effect; wash effect
 - Integrated show programs
 - The device is cooled by cooling fan
 - Control via IR remote control; DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 18°
 - With double bracket
 - 4 digit 7-segment LED display
 - Preprogrammed in Light´J; Light Captain; Colorchief
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397669305
Weight: 1,30 kg
Length: 0.19 m
Width: 0.19 m
Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	20 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	IR remote control; DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	65°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 21,5 cm Depth: 12,7 cm Height: 22,8 cm
Weight:	1,10 kg
Noise classification:	Class 3 (clearly perceptible sounds); class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 2 x Ø10mm
Material:	Metal, 1,5 mm
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting
