eurolite®

EUROLITE LED PST-12W 6000K Spot

Narrow beam pinspot with 12 W cold white (CW) LED

Art. No.: 51916010 GTIN: 4026397735932











List price: 47.48 €

incl. 19% VAT.

Features:

- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- 1 powerful LED 12 W COB (chip-on-board) cold white (CW)
- Focus manual; zoom manual
- Spot effect
- The device is cooled by passive convection cooling
- Control via plug and play
- Silent operation
- Application possibility: Suspended; on stand; wall mounting
- Very high color rendering index (CRI)
 Package contents
- 1 x spotlight, 1 x user manual

Technical specifications:

100-240 V AC, 50/60 Hz
12 W
IP20
Protection class I
Fixed power supply cord with safety plug
LED lamp

Logistic

EAN / GTIN: 4026397735932 Weight: 0,45 kg Length: 0.19 m Width: 0.18 m Heigth: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Equipment: Focus manual; zoom manual Cooling: Passive convection cooling Control: Plug and play Beam angle: 12° Beam angle (1/2 peak): Spot 12° monochrome Spot 10° monochrome Spot 10° monochrome Spot 10° monochrome Spot 12° Beam angle (1/10 peak): Spot 16° Spot 12° Spot 12° Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (Ix): Cold white (CW) 1m: 5138 Ix, 3m: 541 Ix, 6m: 145 Ix Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting: metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Width: 8,5 cm Height: 0,44 kg Noise classification: Class 0 (no noise at all) </th <th>LED type:</th> <th>1 x 12 W COB (chip-on-board) cold white (CW)</th>	LED type:	1 x 12 W COB (chip-on-board) cold white (CW)
Control: Plug and play Beam angle: 12° Beam angle (1/2 peak): Spot 12° monochrome Spot 10° monochrome Spot 11° monochrome Spot 7° monochrome Spot 12° Beam angle (1/10 peak): Spot 16° Spot 11° Spot 12° Spot 12° Spot 12° Spot 9° Color temperature: Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (Ix): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Lu Illuminance in Lux (Ix): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 3 x 0,75 mm² H05VV-F Cable construction: 3 x 0,75 mm² H05VV-F	Equipment:	Focus manual; zoom manual
Beam angle: 12° Beam angle (1/2 peak): Spot 12° monochrome Spot 10° monochrome Spot 10° monochrome Spot 7° monochrome Spot 14° Spot 12° Spot 9° Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (lx): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 lm rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Width: 8,5 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 3 x 0,75 mm² H05VV-F Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket<	Cooling:	Passive convection cooling
Beam angle (1/2 peak): Spot 12° monochrome Spot 10° monochrome Spot 10° monochrome Spot 7° monochrome Spot 14° Spot 12° Spot 14° Spot 12° Spot 12° Spot 12° Spot 12° Spot 9° Color temperature: Color rendering index (CRI): 90 Ra Illuminance in Lux (lx): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Weight: Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable length: Approx. 1 m Mounting bracket Mounting bracket	Control:	Plug and play
Spot 11° monochrome Spot 10° monochrome Spot 7° monochrome Beam angle (1/10 peak): Spot 16° Spot 12° Spot 12° Spot 9° Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (tx): Cold white (CW) 1m: 5138 kx, 3m: 541 kx, 6m: 145 kx Lurninous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable length: Approx. 1 m Mounting bracket	Beam angle:	12°
Spot 10° monochrome Beam angle (1/10 peak): Spot 16° Spot 14° Spot 12° Spot 9° Color temperature: 6000K 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (lx): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 lm rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable length: Approx. 1 m Mouning bracket	Beam angle (1/2 peak):	Spot 12° monochrome
Spot 7° monochromeBeam angle (1/10 peak):Spot 16° Spot 12° Spot 9°Color temperature:6000KColor rendering index (CRI):90 RaIlluminance in Lux (lx):Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMouning bracket		
Beam angle (1/10 peak): Spot 16° Spot 12° Spot 9° Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (lx): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket Mounting bracket		
Spot 14° Spot 12° Spot 9° Color temperature: 6000K Color rendering index (CRI): 90 Ra Illuminance in Lux (Ix): Cold white (CW) 1m: 5138 Ix, 3m: 541 Ix, 6m: 145 Ix Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable length: Approx. 1 m Mounting bracket Mounting bracket		Spot 7° monochrome
Spot 12° Spot 9°Color temperature:6000KColor rendering index (CRI):90 RaIlluminance in Lux (Ix):Cold white (CW) 1m: 5138 Ix, 3m: 541 Ix, 6m: 145 IxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket	Beam angle (1/10 peak):	Spot 16°
Spot 9°Color temperature:6000KColor rendering index (CRI):90 RaIlluminance in Lux (Ix):Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cmWidth: 8,5 cmHeight: 13,5 cmDiameter: Ø 6 cmDiameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cordCable construction:Cable length:Approx. 1 mMounting bracket		Spot 14°
Color temperature:6000KColor rendering index (CRI):90 RaIlluminance in Lux (Ix):Cold white (CW) 1m: 5138 Ix, 3m: 541 Ix, 6m: 145 IxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket		
Color rendering index (CRI):90 RaIlluminance in Lux (lx):Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cmWidth: 8,5 cmHeight: 13,5 cmDiameter: Ø 6 cmDiameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracketMounting bracket		Spot 9°
Illuminance in Lux (lx): Cold white (CW) 1m: 5138 lx, 3m: 541 lx, 6m: 145 lx Luminous flux: 1200 Im rated light flux at 90° Housing color: Black matte Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable length: Approx. 1 m Mounting bracket Mounting bracket	Color temperature:	6000K
IxLuminous flux:1200 Im rated light flux at 90°Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable construction:3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket	Color rendering index (CRI):	90 Ra
Housing color:Black matteMaterial:Aluminum casting; metal; plasticDimensions:Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord3 x 0,75 mm² H05VV-FCable construction:3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket	Illuminance in Lux (lx):	
Material: Aluminum casting; metal; plastic Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 3 x 0,75 mm² H05VV-F Cable construction: 3 x 0,75 mm² H05VV-F Mounting bracket Mounting bracket	Luminous flux:	1200 lm rated light flux at 90°
Dimensions: Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm Diameter: Ø 6 cm Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 3 x 0,75 mm² H05VV-F Cable construction: 3 x 0,75 mm² H05VV-F Mounting bracket Mounting bracket	Housing color:	Black matte
Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cord2035437Cable construction:3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket	Material:	Aluminum casting; metal; plastic
Height: 13,5 cm Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cordCable construction:3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket	Dimensions:	Length: 19 cm
Diameter: Ø 6 cmWeight:0,44 kgNoise classification:Class 0 (no noise at all)Energy efficiency class (A - G):EEPREL-Nr:2035437Power cordCable construction:Cable construction:3 x 0,75 mm² H05VV-FCable length:Approx. 1 mMounting bracket		Width: 8,5 cm
Weight: 0,44 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket Mounting bracket		Height: 13,5 cm
Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord Cable construction: Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket Image: Class 0 (no noise at all)		Diameter: Ø 6 cm
Energy efficiency class (A - G): E EPREL-Nr: 2035437 Power cord 2035437 Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket 1	Weight:	0,44 kg
EPREL-Nr: 2035437 Power cord	Noise classification:	Class 0 (no noise at all)
Power cord Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket Mounting bracket	Energy efficiency class (A - G):	E
Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1 m Mounting bracket Approx. 1 m	EPREL-Nr:	2035437
Cable length: Approx. 1 m Mounting bracket	Power cord	
Mounting bracket	Cable construction:	3 x 0,75 mm² H05VV-F
	Cable length:	Approx. 1 m
Diameter mounting holes: 1 x Ø10mm	Mounting bracket	
	Diameter mounting holes:	1 x Ø10mm