#### Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

# eurolite

# EUROLITE LED IP PST-10W 6400K Pinspot

Weather-proof pinspot (IP65) with strong 10 W LED in cold white (CW)

Art. No.: 51916158 GTIN: 4026397617726

List price: 71.28 €

incl. 19% VAT.

### Features:

- Compact aluminum housing
- 1 powerful LED 10 W high-power cold white (CW) \_
- Beam effect \_
- The device is cooled by passive convection cooling -
- Control via plug and play -
- With a beam angle of 4°
- With mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended -Package contents
- 1 x device, 1 x user manual

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,9 m

#### Logistic

EAN / GTIN: 4026397617726 Weight: 0,80 kg Length: 0.17 m Width: 0.12 m Heigth: 0.11 m









Lamp type:	LED lamp
LED type:	1 x 10 W high-power cold white (CW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	4°
Beam angle (1/2 peak):	4°
Beam angle (1/10 peak):	6°
Color temperature:	6400K
Illuminance in Lux (lx):	1m: 39687 lx, 3m: 4446 lx, 6m: 1255 lx
Luminous flux:	887 lm
Housing color:	Grey
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 10,5 cm
	Depth: 15 cm
	Height: 14,7 cm
Weight:	0,75 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1064813
Mounting bracket	
Diameter mounting holes:	3 x Ø6mm
Material:	Aluminum, 2 mm