

EUROLITE LED PST-40 QCL Spot

LED spotlight with RGBW color mixing, IR remote control and 2 frost filters

Art. No.: 51916170

GTIN: 4026397710625



List price: 224.91 €

incl. 19% VAT.

Features:

- Two additional frost filters provide a soft, homogeneous light
- 3 buttons on the remote control for saving your own settings
- 1 powerful LED 40 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 4°
- With double bracket
- OLED display
- Silent operation
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; installation; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 2 x frost filter, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397710625

Weight: 2,22 kg

Length: 0.19 m

Width: 0.17 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	36 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
LED type:	1 x 40 W 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 20° Frost filter 80°
Beam angle (1/10 peak):	8°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Dimensions:	Length: 12 cm Width: 17 cm Height: 22,5 cm
Weight:	1,98 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting