

EUROLITE LED DMF-4 Hybrid Flower Effect

Spotlight with flower- and stroboscope effect, incl. IR remote control

Art. No.: 51918563

GTIN: 4026397695052



List price: 95.08 €

incl. 19% VAT.

Features:

- 2 strips with white LEDs provide fast, dynamic strobe effects
 - 70 powerful LEDs 5 mm R/G/B
 - 12 powerful LEDs SMD 5050 cold white (CW)
 - Flower effect; strobe effect
 - 4 integrated show programs
 - Direct color selection for 8 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; IR remote control; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light Captain
 - With a beam angle of 37°
 - Good color rendering index (CRI)
 - With mounting bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; party room; small rental
 - Very quiet working noise
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x device, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397695052

Weight: 1,45 kg

Length: 0.23 m

Width: 0.22 m

Height: 0.13 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Fuse:	T 0,5 A fuse replaceable
LED type:	70 x 5 mm R/G/B 12 x SMD 5050 cold white (CW)
DMX channels:	7
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Beam angle:	37°
Beam angle (1/2 peak):	37°
Color rendering index (CRI):	80 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 19,4 cm Width: 20,2 cm Height: 12,3 cm
Weight:	1,30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting