# eurolite®

## EUROLITE LED CAT-80 Beam Effect wh

LED beam effect with cold white 80 W COB LED and gobo wheel

Art. No.: 51918596 GTIN: 4026397719635











## List price: 379.61 €

incl. 19% VAT.

#### Features:

#### - 3 different motion axes

- Rotating faceted mirror inside
- Rotating and swiveling mirror cylinder
- Generates countless moving patterns in the room
- 1 powerful LED 80 W COB (chip-on-board) cold white (CW)
- Gobo wheel with static gobos; focus manual
- Dimmer electronic
- Mirror cylinder effect; strobe effect
- Gobo wheel with static gobos, 9 color gobos and open
- The device is cooled by cooling fan
- Control via stand-alone; master/slave function; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- OLED display
- For application areas such as: Clubs/dancing school; party room; stage; mobile djs / entertainer; rental
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x XLR cable

#### Logistic

EAN / GTIN: 4026397719635 Weight: 4,08 kg Length: 0.40 m Width: 0.35 m Heigth: 0.24 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

### Technical specifications:

| Power supply:         | 100-240 V AC, 50/60 Hz  |
|-----------------------|---|
| Power consumption:    | 110 W   |
| IP classification:    | IP20  |
| Protection class:     | Protection class I  |
| Power connection:     | Mains input via P-Con (blue), mounting version power supply cord with safety plug   |
| Fuse:                 | 5 x 20 mm, T 2 A fuse replaceable   |
| Lamp type:            | LED lamp  |
| LED type:             | 1 x 80 W COB (chip-on-board) cold white (CW)  |
| Flash rate:           | 0 - 25 Hz   |
| Equipment:            | Gobo wheel with static gobos; focus manual  |
| Gobos:                | Gobo wheel with static gobos, 9 color gobos and open  |
| DMX channels:         | 7   |
| DMX input:            | 3-pin XLR (M) mounting version  |
| DMX output:           | 3-pin XLR (F) mounting version  |
| Cooling:              | Cooling fan   |
| Control:              | Stand-alone; master/slave function; sound to light<br>via microphone; DMX; QuickDMX via USB<br>(optional); W-DMX by wireless solution via USB<br>(optional); CRMX by LumenRadio via USB<br>(optional) |
| Preprogrammed in:     | Light J; Light Captain; EASY SHOW 2; EASY<br>SHOW 3; Colorchief   |
| Projection:           | Flicker-free  |
| Housing color:        | White   |
| Display type:         | OLED display  |
| Dimensions:           | Width: 29,0 cm<br>Depth: 18,5 cm<br>Height: 31,5 cm   |
| Weight:               | 3,12 kg   |
| Noise classification: | Class 3 (clearly perceptible sounds)  |
| Legal specifications  |   |
| Special product:      | Not designed for household room illumination  |
| Intended use:         | Show effect lighting  |