

## EUROLITE LED CBB-6 COB RGB Bar

LED light effect bar with RGB color mixing, incl. IR remote control

Art. No.: 51930279

GTIN: 4026397653762



List price: 355.81 €

incl. 19% VAT.

### Features:

- 6 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - Integrated show programs
  - Direct color selection for 18 preset colors
  - The device is cooled by low-noise cooling fan
  - Control via IR remote control; sound to light via microphone; master/slave function; DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 38°
  - With mounting bracket
  - 4 digit 7-segment LED display
  - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397653762

Weight: 7,10 kg

Length: 0.72 m

Width: 0.24 m

Height: 0.21 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	6 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5; 9; 18; 21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	IR remote control; sound to light via microphone; master/slave function; DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 68,5 cm Depth: 16,5 cm Height: 20,0 cm
Weight:	6,20 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting