

EUROLITE LED CBT-6 COB TCL Tower

LED light effect column with RGB color mixing, incl. IR remote control

Art. No.: 51930281

GTIN: 4026397670776



List price: 474.81 €

incl. 19% VAT.

Description:

LED lighting column with RGB color mixing

The flicker-free LED tower EUROLITE LED CBT-6 COB TCL with integrated DMX control unit is equipped with six powerful 30 W COB LEDs in RGB. Thanks to its slim design and the included carrying bag, it is especially suitable for mobile applications, such as solo entertainers or mobile DJs. Thanks to the tripod sleeve, the CBT-6 is suitable for tripod mounting, but you can also place the CBT-6 directly on the floor.

In the auto and music mode you can play integrated show programs. You have direct color selection for 18 colors. Further functions are color change, color fading, dimmer and strobe effects.

The LED light effect column is compatible with QuickDMX, the wireless DMX system from Eurolite. A phantom-powered USB socket for wireless transmission of the DMX signal via a QuickDMX receiver is located on the back of the device.

The integrated control unit with a four-digit LED display allows you to address and adjust the LED tower. The control can be done either by DMX, QuickDMX via USB, by the integrated music control, with the master/slave function or with the included infrared remote control. The P-Con mains connections allow you to easily connect up to eight devices in series.

Features:

- LED tower with integrated DMX control unit and stand sleeve for tripod installation
- 6 powerful LEDs COB (chip-on-board) 3in1 TCL RGB
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; multi beam effect
- Integrated show programs
- Direct color selection for 18 preset colors

Logistic

EAN / GTIN: 4026397670776

Weight: 9,20 kg

Length: 1.04 m

Width: 0.26 m

Height: 0.26 m

- The device is cooled by low-noise cooling fan
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 38°
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual, 1 x remote control, 1 x battery, 1 x bag

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 100 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version |
| Power output: | 1 x P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A |
| Lamp type: | LED lamp |
| LED type: | 6 x COB (chip-on-board) 3in1 TCL RGB |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 3; 5; 18; 9; 21 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Low-noise cooling fan |
| Control: | DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 38° |
| Beam angle (1/2 peak): | 38° |
| Beam angle (1/10 peak): | 70° |
| Housing color: | Black |
| Dimensions: | Width: 17 cm Depth: 15 cm Height: 96 cm |
| Weight: | 7,60 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

Legal specifications

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |