

EUROLITE LED Silent Bar 16x4W RGB/WW

Compact and whisper-quiet spotlight for colored and white light

Art. No.: 51930370

GTIN: 4026397731118



List price: 189.21 €

incl. 19% VAT.

Features:

- 16 powerful LEDs 4 W SMD 3535 4in1 QCL RGB/WW
 segments controlled separately
- Additional frost filter provides a wide, soft and homogeneous light
- Color blend stepless; color change automatic; color fade automatic; Dimmer electronic; program speed adjustable
- Wash effect; strobe effect
- 41 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; IR remote control (not included); DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 20°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand
- Preprogrammed in Colorchief; Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Good color rendering index (CRI)

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x frost filter

Logistic

EAN / GTIN: 4026397731118

Weight: 3,05 kg

Length: 0.38 m

Width: 0.29 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1,6 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Lamp type:	LED lamp
LED type:	16 x 4 W SMD 3535 4in1 QCL RGB/WW
Flash rate:	1 - 25 Hz
DMX channels:	4; 6; 8; 16; 18; 20
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control (not included); DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Colorchief; Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20° Frost filter 30°
Beam angle (1/10 peak):	50° Frost filter 80°
Color rendering index (CRI):	83 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 33 cm Width: 17 cm Depth: 17 cm
Weight:	2,73 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting