


EUROLITE LED BAR-6 UV Bar

LED bar (50cm) with 6 x 1 watt ultra violet (UV) LED

Art. No.: 51930391

GTIN: 4026397665727



List price: 112.93 €

incl. 19% VAT.

Description:

Light effect bar (50 cm) with UV LEDs

The powerful and dimmable light effect bar EUROLITE LED BAR-6 UV is equipped with six 1 W UV LEDs. Due to the convection cooling, the LED BAR is noiseless and offers you versatile application possibilities. Whether at events or for band performances - whether in the theatre or at galas - the LED Bar-6 UV is variably applicable.

It is controlled via DMX, master-slave operation is also possible. The LED Bar also has a phantom-powered USB socket for a QuickDMX receiver. This is optionally available. In auto and music mode you can also use integrated show programs.

Addressing and settings can be made via the integrated control unit with 4-digit LED display.

The mains connections allow you to operate up to eight devices in a row.

Logistic

EAN / GTIN: 4026397665727

Weight: 1,83 kg

Length: 0.54 m

Width: 0.14 m

Height: 0.11 m

Features:

- 6 powerful LEDs 1 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 14°
- With mounting bracket
- Silent operation
- Preprogrammed in LED PC-Control 512; Colorchief

- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Application possibility: Suspended; wall mounting

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 2 x mounting bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 1 W high-power ultra violet (UV)
DMX channels:	1; 2
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; Colorchief
Projection:	Flicker-free
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/2 peak):	Wash effect
Beam angle (1/10 peak):	24°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 50 cm Depth: 8,5 cm Height: 11,5 cm
Weight:	1,65 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting